

# 9490

Remote Area Lighting Systems from Peli are the complete lighting solution for first responders, industrial and aerospace applications.

- Built Peli tough
- Full time battery level indication with low level flashing indicator
- Deployable mast with 340 degree rotation
- Multiple deployment positions
- Convenient shoulder strap
- Quick release / Hot swappable battery design with 12 volt power supply
- Up to 6,000 lumens (calculated)
- Up to 24 hrs of run time
- Intelligent Control (allows for various light output levels)



#### **DIMENSIONS**

Head (L×W×D) 8.25 x 5.75" x 2.25 (21 x 14.6 x 5.7 cm) Closed (L×W×D) 20.00 x 6.50" x 11.25 (50.8 x 16.5 x 28.6 cm)

**Light Head Height** (max)

72.00" (182.9 cm)

#### **MATERIALS**

**Body** Polypropylene Aluminum Head Mast Aluminum

Polycarbonate (PC) Lens

### **COLOURS**

Black Yellow

#### LIGHT SPECS

Lumens (High) 6000 **Lamp Heads** LED **Lamp Type** Number of LEDs 10 **Beam Spread** 125° **IP Rating** 54

### **POWER**

Run Time (High) 3.50 hrs Run Time (Med) 12.00 hrs Run Time (Low) 24.00 hrs

**Battery Type** Sealed Lead Acid (SLA)

Rechargeable yes **Battery Lifespan** 500 cycles Charge Time 8 hrs

**Battery Level Indicator** Full-time battery level display and low battery warning (visible flashing)

Sockets (Primary) 1 Volts 12.0v

### WEIGHT

**Weight** 32.00 lbs (14.5 kg)

# **SWITCH**

Switch TypeSilicone Rubber KeypadLight ModesHigh / Medium / Low / Flashing

# **ACCESSORIES**



**9483** Power Supply



**9487** Padded Shoulder Strap



**9489** Powerpack



**9447** DC Vehicle Charger Cord

#### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 12-03-25