



9430

Remote Area Lighting Systems from Peli are the complete lighting solution for first responders, industrial and aerospace applications.

- Built Peli tough
- New improved version - Generation 3
- Up to 15 hours of run time
- 3000 lumens of brightness
- Fully extendable mast with 360 degree rotating head
- Low Battery Warning System
- Waterproof Rubber Activation Switch
- Mast Extension Lock
- RoHS and CE Compliant
- Includes 110 - 240 Volt (50/60hz) charger and universal adaptors



DIMENSIONS

Head (LxWxD)	6.50 x 7.87" x 2.56 (16.5 x 20 x 6.5 cm)
Closed (LxWxD)	15.75 x 7.87" x 9.06 (40 x 20 x 23 cm)
Light Head Height (max)	32.28" (82 cm)
Cord Length	13.78" (35 cm)

MATERIALS

Body	Polycarbonate (PC) / ABS
Head	Polycarbonate (PC) / ABS
Mast	Glass-Reinforced Plastic
Lens	Polycarbonate (PC)

COLOURS

 Black	 Yellow
---	--

LIGHT SPECS

Lumens (High)	3000
Lumens (Low)	1500
Lamp Heads	1
Lamp Type	LED
Number of LEDs	6
Beam Spread	125°
IP Rating	54

POWER

Run Time (High)	8.00 hrs
Run Time (Low)	15.00 hrs
Battery Type	Sealed Lead Acid (SLA)
Rechargeable	yes
Battery Lifespan	500 cycles
Battery Level Indicator	Intermittent Blinking

Sockets (Primary)	1
Sockets (Aux)	1
Volts	12.0v

WEIGHT

Weight	22.65 lbs (10.3 kg)
---------------	---------------------

SWITCH

Switch Type	Silicone Rubber Keypad
--------------------	------------------------

ACCESSORIES



1460AALG

1460 Case with custom fit foam



9430TP

Tripod



9436B

12/24V Vehicle Charger



9437B

Extension Cord (black connector)
118in (3m)

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 09-17-25