



5050R

Get local to long distance in a slide. The new Peli™ 5050R flashlight features flood to spot technology: Flood position projects a wide beam to illuminate your work area and spot beam for a long distance focused beam. Get power for the work day and your smartphone. Recharge the 5050R by connecting directly to its Micro USB port. Or connect to a USB port to power your smartphone or any other USB powered device. The 5050R: it's our rechargeable option that can add some jolt to your text conversations.

- Lithium Ion Rechargeable Battery
- 4 modes: Boost / High / Low / Flashing
- Up to 201m Beam Distance
- Up to 883 Lumens



DIMENSIONS

Length	6.16" (15.6 cm)
---------------	-----------------

MATERIALS

Body	Aluminum with Type II Anodized
O-Ring	NBR
Lens	AR Coated Glass
Shroud	Aluminum with Type II Anodized

COLOURS

■ Black

LIGHT SPECS

Lamp Type	LED
------------------	-----

POWER






Battery Size	18650
Battery Type	Lithium
Battery Quantity	1
Batteries Included	yes
Rechargeable	yes
Charge Time	6 hrs
Battery Level Indicator	Full-time battery indicator
Volts	3.7v

WEIGHT

Weight With Batteries	5.8 oz (164 gr)
Weight Without Batteries	4.1 oz (116 gr)

SWITCH

Switch Type Push Button
Light Modes Boost / High / Low / Flashing

FL1 STANDARD	HIGH	LOW	BOOST
	393 LUMENS	21 LUMENS	883 LUMENS
	2h 30mins	40h 0mins	0h 0mins
	134m	30m	201m
	4488cd	224cd	10093cd
	IPX8 (1m)		

ACCESSORIES



2389
Replacement Battery

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 11-21-24