

EU060060-3010

ISP2 Case

Shifting loose cargo can slow down your ops and threaten the mission with damaged freight. The ISP² Case from Peli™ virtually eliminates load movement with a unique Inter-Stacking Pattern (ISP). The system is compatible across 64 different case sizes, from 0,018 to 0,576 cubic metres of storage. Equipped with a silicone sponge O-ring and pressure release valves, the ISP² Case is impervious to extreme weather and wet conditions.

The system is designed to maximize the volume of standard logistics platforms. Whether loading standard pallets, NATO pallets, JMIC containers, 463L pallets or sea containers, the ISP² Case system will make the most efficient use of cargo space.

With its Inter-Stacking Pattern, ISP2 Cases can be cubed out as a solid block. The 10x10cm squared pattern bottom matches with the cube pattern on the case below, literally falling and locking into place.

- Made in Europe
- · Inter-stacking pattern to keep loads tigh
- Maximizes the volume of standard logistics platforms
- Moulded-in, tongue-in-groove gasketed parting lines for splash resistance and tight seals, even after impact
- Positive anti-shear locks, which prevent lid separation after impact, and reduce stress on hardware



DIMENSIONS

Interior (L×W×D) 20.28 x 20.28" x 14.57 (51.5 x 51.5 x 37 cm) Exterior (L×W×D) 23.62 x 23.62" x 15.75 (60 x 60 x 40 cm)

 Lid Depth
 3.94" (10 cm)

 Bottom Depth
 11.81" (30 cm)

 Total Depth
 15.75" (40 cm)

 Int Volume
 3.47 ft³ (0.098 m³)

MATERIALS

BodyRotoMolded PolyethyleneLatchSteel (Zinc Cobalt-Black-Plated)

O-Ring Silicone Sponge
Pins Stainless Steel
Pins (Alt) Aluminum

Purge Body Mechanical PRV - Aluminum Body

COLOURS

Black - 032 Fed Std

27040

Red - 130 Fed Std

21105

Green - 138 Fed Std

24052

Blue - 101 Fed Std

25052

Olive Drab - 137 Fed

Std 34096

Blue - 135 Pantone

292U

Orange - 134 Fed Std

12197

Gray - 133 Fed Std

26270

White - 132 Fed Std

27925

Yellow - 131 Fed Std

23538

Tan - 250 Fed Std

20372

Yellow - 136 Pantone

012U

Maroon - 197 Pantone

202U

WEIGHT

 Weight Empty
 23.37 lbs (10.6 kg)

 Buoyancy
 278.22 lbs (126.2 kg)

TEMPERATURE

Minimum Temperature -22°F (-30 °C) **Maximum Temperature** 158°F (70 °C)

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 07-31-25