

1700

Protector

Long Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Strong polyurethane wheels with stainless steel bearings
- Watertight, crushproof, and dustproof
- 3-piece foam set
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down side handle
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors



CONFIGURATIONS







1700NF No Foam



1700WF With Foam

DIMENSIONS

Interior (L×W×D) 35.75 x 13.50" x 5.25 (90.8 x 34.3 x 13.3 cm) Exterior (L×W×D) 38.12 x 16.00" x 6.12 (96.8 x 40.6 x 15.5 cm)

 Lid Depth
 1.75" (4.4 cm)

 Bottom Depth
 3.50" (8.9 cm)

 Total Depth
 5.25" (13.3 cm)

 Int Volume
 1.47 ft³ (0.042 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

MATERIALS

Body Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

COLOURS

Black OD Green

WEIGHT

Weight With Foam 16.98 lbs (7.7 kg) Weight Empty 16.09 lbs (7.3 kg) Buoyancy 136.91 lbs (62.1 kg) **Master Pack Weight** 19.10 lbs (8.7 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

CERTIFICATIONS

IP67

MIL C-4150J Def Stan 81-41

OTHER

2 Wheels **Master Pack** 1 Military yes

ACCESSORIES



3 pc. Replacement Foam Set

1701



1703 Replacement O-ring



1506TSA TSA Lock



1500D Desiccant Silica Gel



LGMT-001P Protector Case Roof Mount

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 08-27-25