


1620EU

Protector

The Peli 1620 is a large sized protector case that comes with comfortable wheels and retractable handle, as well as with 2 comfortable side carrying handles, 4 double-step latches -which are secure, but easy to open when needed, an automatic purge valve -that equalizes air pressure, 2 strong wheels, a watertight silicone O-ring lid and stainless steel hardware. Rugged, uncompromising and trusted, Peli cases protect what matters to you, from the everyday to the extraordinary. Peli Protector Cases are made with copolymer polypropylene and cutting edge technology, which makes them virtually indestructible and resistant to the most extreme conditions. Proven for over 45 years in the most demanding environments. Engineered and manufactured in the U.S and in Germany. Guaranteed for Life and sustainable due to its long life.



- · Watertight, crushproof, and dustproof
- 4 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors
- Made in Germany



CONFIGURATIONS



1620EU Standard



1624With Padded Dividers



1620NF No Foam



1620WF With Foam

DIMENSIONS

Interior (L×W×D) 21.37 x 16.31" x 12.56 (54.3 x 41.4 x 31.9 cm) Exterior (L×W×D) 24.81 x 19.37" x 13.87 (63 x 49.2 x 35.2 cm)

 Lid Depth
 2.06" (5.2 cm)

 Bottom Depth
 10.50" (26.7 cm)

 Total Depth
 12.56" (31.9 cm)

 Int Volume
 2.53 ft³ (0.072 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

MATERIALS

Body

Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS

Black

WEIGHT

 Weight With Foam
 26.01 lbs (11.8 kg)

 Weight Empty
 24.47 lbs (11.1 kg)

 Buoyancy
 149.91 lbs (68 kg)

 Master Pack Weight
 26.90 lbs (12.2 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

CERTIFICATIONS

IP67

MIL C-4150J Def Stan 81-41

OTHER

Wheels 2
Extendable Handle yes
Master Pack 1
Nameplate yes
Military yes

ACCESSORIES



1609 Lid Organizer



1621 6 pc. Replacement Foam Set



1623 Replacement O-ring



1625 Padded Divider Set



1507 Quick Mounts - set of 4



1506TSA TSA Lock



1500D Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 08-10-25