

AL2727-1409AC

Trusted for over 40 years by the US Military, Single Lid Cases offer 20% more protective material in the edges and corners, where it is needed most, ensuring that valuable equipment is kept safe from any unforeseen elements. Available in several sizes, these cases are completely customizable with a wide range of bolt-on options like document holders, casters, humidity indicators and much more.

• Molded-in, tongue-in-groove gasketed parting lines for splash resistance and tight seals, even after impact

· Reinforced corners and edges for additional impact protection

• Molded-in ribs and corrugations for secure, non-slip stacking, columnar strength, and added protection

• Recessed hardware for extra protection

• Positive anti-shear locks, which prevent lid separation after impact, and reduce stress on hardware

• Patented molded-in metal inserts for catch and hinge attachment points, which provide strength and spread loads to the container

One-piece construction, molded from lightweight, high-impact polyethylene



DIMENSIONS

Interior (L×W×D)	27.00 x 27.00" x 23.37 (68.6 x 68.6 x 59.4 cm)
Exterior (L×W×D)	30.00 x 30.00" x 25.56 (76.2 x 76.2 x 64.9 cm)
Lid Depth	9.25" (23.5 cm)
Bottom Depth	14.12" (35.9 cm)
Total Depth	23.37" (59.4 cm)
Int Volume	9.86 ft³ (0.279 m³)

MATERIALS

Body	RotoMolded Polyethylene			
Latch	Steel (Nickel-black Plated)			
O-Ring	Silicone Sponge			
Foam	No Foam, empty case standard Optional PE and PU, 1 and 2 lb. options filled and lined			
Purge Body	Aluminum			
Handle	Heavy Duty Injection Molded Standard			
Hardware	Yellow Carbon Steel Standard			

COLOURS

Gray - 133 Fed Std 26270

WEIGHT

Weight	41.10 lbs (18.6 kg)
Buoyancy	790.03 lbs (358.4 kg)
Master Pack Weight	43.10 lbs (19.5 kg)

TEMPERATURE

Minimum Temperature	-20°F (-28.9 °C)	
Maximum Temperature	140°F (60 °C)	

OTHER

Military	yes				
----------	-----	--	--	--	--

Peli c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 06-28-25