



1010 Micro

From small sensitive components to smartphones, protect your gear from the elements in a crushproof, watertight, & dustproof Micro Case from Peli.

- ***Case is able to be submerged under 1 meter of water for up to 30 minutes in accordance with IP67 testing parameters**
- **Available in clear with color liner or solid**
- **Watertight, crushproof, and dustproof**
- Carabiner
- Easy open latch
- Rubber liner for extra protection doubles as o-ring seal
- Peli's legendary lifetime guarantee**
- * Where applicable by law



DIMENSIONS

| | |
|-------------------------|--|
| Interior (LxWxD) | 4.37 x 2.87" x 1.68 (11.1 x 7.3 x 4.3 cm) |
| Exterior (LxWxD) | 5.88 x 4.06" x 2.12 (14.9 x 10.3 x 5.4 cm) |
| Lid Depth | 0.69" (1.8 cm) |
| Bottom Depth | 0.94" (2.4 cm) |
| Total Depth | 1.63" (4.1 cm) |
| Int Volume | 0.01 ft ³ (0 m ³) |

MATERIALS

| | |
|-------------------|--------------------------------------|
| Body | Polycarbonate (PC) |
| Latch | Xylex |
| O-Ring | Thermoplastic Rubber |
| Pins | Stainless Steel |
| Foam | TL - 426 4 lb. Esther |
| Purge Body | Polycarbonate (PC) |
| Purge Vent | Polyester Spun-Bond ePTFE Oleophobic |

COLOURS

| | | | |
|----------------|---------------|-----------------|------------------|
| ■ Black | ■ Blue | ■ Black - Clear | ■ Yellow - Clear |
| ■ Blue - Clear | ■ Red - Clear | | |

WEIGHT

| | |
|---------------------------|-------------------|
| Weight With Foam | 0.41 lbs (0.2 kg) |
| Weight Empty | 0.40 lbs (0.2 kg) |
| Buoyancy | 0.51 lbs (0.2 kg) |
| Master Pack Weight | 3.06 lbs (1.4 kg) |

TEMPERATURE

| | |
|----------------------------|------------------|
| Minimum Temperature | -10°F (-23.3 °C) |
| Maximum Temperature | 199°F (92.8 °C) |

CERTIFICATIONS

IP67

OTHER

| | |
|---------------------|-----|
| Minimum Pack | 6 |
| Master Pack | 6 |
| Military | yes |

ACCESSORIES



1012
Pick N Pluck™ Foam Insert

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 04-03-25