



## 9430

Remote Area Lighting Systems from Peli are the complete lighting solution for first responders, industrial and aerospace applications.

- Built Peli tough
- New improved version - Generation 3
- Up to 15 hours of run time
- 3000 lumens of brightness
- Fully extendable mast with 360 degree rotating head
- Low Battery Warning System
- Waterproof Rubber Activation Switch
- Mast Extension Lock
- RoHS and CE Compliant
- Includes 110 - 240 Volt (50/60hz) charger and universal adaptors



### DIMENSIONS

<b>Head (LxWxD)</b>	6.50 x 7.87" x 2.56 (16.5 x 20 x 6.5 cm)
<b>Closed (LxWxD)</b>	15.75 x 7.87" x 9.06 (40 x 20 x 23 cm)
<b>Light Head Height (max)</b>	32.28" (82 cm)
<b>Cord Length</b>	13.78" (35 cm)

### MATERIALS

<b>Body</b>	Polycarbonate (PC) / ABS
<b>Head</b>	Polycarbonate (PC) / ABS
<b>Mast</b>	Glass-Reinforced Plastic
<b>Lens</b>	Polycarbonate (PC)

### COLOURS

 Black	 Yellow
---	--

### LIGHT SPECS

<b>Lumens (High)</b>	3000
<b>Lumens (Low)</b>	1500
<b>Lamp Heads</b>	1
<b>Lamp Type</b>	LED
<b>Number of LEDs</b>	6
<b>Beam Spread</b>	125°
<b>IP Rating</b>	54

### POWER

<b>Run Time (High)</b>	8.00 hrs
<b>Run Time (Low)</b>	15.00 hrs
<b>Battery Type</b>	Sealed Lead Acid (SLA)
<b>Rechargeable</b>	yes
<b>Battery Lifespan</b>	500 cycles
<b>Battery Level Indicator</b>	Intermittent Blinking

<b>Sockets (Primary)</b>	1
<b>Sockets (Aux)</b>	1
<b>Volts</b>	12.0v

---

## WEIGHT

<b>Weight</b>	22.65 lbs (10.3 kg)
---------------	---------------------

---

## SWITCH

<b>Switch Type</b>	Silicone Rubber Keypad
--------------------	------------------------

---

## ACCESSORIES



**1460AALG**  
1460 Case with custom fit foam



**9430TP**  
Tripod



**9436B**  
12/24V Vehicle Charger



**9437B**  
Extension Cord (black connector)  
118in (3m)

---

### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 11-22-24*