



# 1560M

## Protector

Mobility Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **4" diameter x 1.5" wide (10.2 x 3.8cm) heavy duty polyurethane wheels with stainless steel bearings**
- **Water resistant, crushproof, and dust resistant**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded top and side handles
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Retractable extension trolley handle
- Stainless steel hardware and padlock protectors
- Peli's legendary lifetime guarantee\*\*
- \* Where applicable by law



## CONFIGURATIONS



**1560M**  
Standard



**1560MNF**  
No Foam



**1560MWF**  
With Foam

## DIMENSIONS

|                              |  |
|------------------------------|--|
| <b>Interior (LxWxD)</b>      | 19.92 x 14.98" x 9.00 (50.6 x 38 x 22.9 cm)    |
| <b>Exterior (LxWxD)</b>      | 23.78 x 18.33" x 12.08 (60.4 x 46.6 x 30.7 cm) |
| <b>Lid Depth</b>             | 2.00" (5.1 cm)                                 |
| <b>Bottom Depth</b>          | 7.00" (17.8 cm)                                |
| <b>Total Depth</b>           | 9" (22.9 cm)                                   |
| <b>Int Volume</b>            | 1.55 ft <sup>3</sup> (0.044 m <sup>3</sup> )   |
| <b>Padlock Hole Diameter</b> | 5/16" (12.7 cm)                                |

## MATERIALS

---

|                   |                                |
|-------------------|--------------------------------|
| <b>Body</b>       | Polypropylene                  |
| <b>Latch</b>      | ABS                            |
| <b>O-Ring</b>     | Polymer                        |
| <b>Pins</b>       | Stainless Steel                |
| <b>Foam</b>       | 1.3 lb Polyurethane            |
| <b>Purge Body</b> | ABS                            |
| <b>Purge Vent</b> | 3 Micron Hydrophobic Non-Woven |

## COLOURS

---

■ Black

## WEIGHT

---

|                         |                    |
|-------------------------|--------------------|
| <b>Weight With Foam</b> | 24.30 lbs (11 kg)  |
| <b>Weight Empty</b>     | 21.30 lbs (9.7 kg) |

## TEMPERATURE

---

|                            |                 |
|----------------------------|-----------------|
| <b>Minimum Temperature</b> | -40°F (-40 °C)  |
| <b>Maximum Temperature</b> | 210°F (98.9 °C) |

## CERTIFICATIONS

---

**IP57**

## OTHER

---


|                          |     |
|--------------------------|-----|
| <b>Wheels</b>            | 2   |
| <b>Extendable Handle</b> | yes |
| <b>Master Pack</b>       | 1   |
| <b>Nameplate</b>         | yes |
| <b>Military</b>          | yes |

## ACCESSORIES

---



**0343**  
Replacement O-ring



**1561**  
4 pc. Replacement Foam Set



**1565**  
Padded Divider Set



**1569**  
Lid Organizer



**1507**  
Quick Mounts - set of 4



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel



**1560TPKIT**  
TrekPak Case Divider Kit



**1560TPDIV**  
Extra TrekPak Dividers

---

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 07-17-24*