

1400EU

Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

These tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

· Watertight, crushproof, and dustproof

- Automatic pressure equalization valve balances interior pressure, keeps water out
- · Comfortable rubber over-molded handle
- · Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck™ with convoluted lid foam
- · Stainless steel padlock protectors
- Made in Germany



CONFIGURATIONS



1400EU Standard



1400WF With Foam



1400NF No Foam

DIMENSIONS

Interior (L×W×D) 11.87 x 8.97" x 5.15 (30.1 x 22.8 x 13.1 cm) Exterior (L×W×D) 13.68 x 11.61" x 5.75 (34.7 x 29.5 x 14.6 cm)

 Lid Depth
 1.18" (3 cm)

 Bottom Depth
 4.00" (10.2 cm)

 Total Depth
 5.18" (13.2 cm)

 Int Volume
 0.32 ft³ (0.009 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

MATERIALS

Body Polypropylene

LatchABSO-RingPolymerPinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS







OD Green

WEIGHT

Weight With Foam 4.41 lbs (2 kg) **Weight Empty** 3.97 lbs (1.8 kg) **Buoyancy** 20.06 lbs (9.1 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

CERTIFICATIONS

IP67 MIL C-4150J

Def Stan 81-41

OTHER

Master Pack 4 Nameplate yes Military yes

ACCESSORIES



1401 3 pc. Replacement Foam Set



1403 Replacement O-ring



1400PF Special Application Panel Frame



1506TSA TSA Lock



1500D Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 12-13-25