



1485

Air

Peli™ Air cases are the first in a series of remarkable innovations engineered by Peli, the pioneers of protective cases. For over 45 years Peli has designed and crafted the most influential protective cases in the world, and we're just getting started.

With the launch of the Peli™ Air line of cases, we're redefining the future of protection with a remarkable union of light and tough.

- Fold down over-molded handle
- Stainless steel padlock protectors
- Press and Pull™ Latches
- Limited Lifetime Warranty
- Super-light proprietary HPX2™ Polymer - up to 40% lighter
- Waterproof O-ring seal
- User-customizable Pick N Pluck™ foam
- User-customizable Pick N Pluck™ foam
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified



CONFIGURATIONS



1485
Standard



1485NF
No Foam



1485WD
With Padded Dividers



1485TP
With TrekPak Divider System



1485WF
With Foam

DIMENSIONS

| | |
|------------------------------|---|
| Interior (LxWxD) | 17.75 x 10.18" x 6.15 (45.1 x 25.9 x 15.6 cm) |
| Exterior (LxWxD) | 19.17 x 12.80" x 6.89 (48.7 x 32.5 x 17.5 cm) |
| Lid Depth | 1.80" (4.6 cm) |
| Bottom Depth | 4.35" (11 cm) |
| Total Depth | 6.15" (15.6 cm) |
| Int Volume | 0.64 ft³ (0.018 m³) |
| Padlock Hole Diameter | 0.31" (0.8 cm) |

MATERIALS

| | |
|-------------------|---|
| Body | Proprietary Polypropylene Blend |
| Latch | ABS |
| O-Ring | EPDM |
| Purge Body | ABS |
| Purge Vent | Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven |

COLOURS

- Black
- Orange
- Silver
- Yellow

WEIGHT

| | |
|-------------------------|---------------------|
| Weight With Foam | 5.39 lbs (2.4 kg) |
| Weight Empty | 4.57 lbs (2.1 kg) |
| Buoyancy | 41.10 lbs (18.6 kg) |

TEMPERATURE

| | |
|----------------------------|------------------|
| Minimum Temperature | -60°F (-51.1 °C) |
| Maximum Temperature | 160°F (71.1 °C) |


ACCESSORIES



1485AirFS
3 pc. Replacement Foam Set



1485AirDS
Padded Divider Set



1485TP-KIT
TrekPak Case Divider Kit



1485TPKIT
TrekPak Case Divider Kit



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 07-17-24