



2780R

Headlamp

The most powerful headlamp in the Peli™ line is now available! Meet the 2780R. With 676 lumens of brilliant light, USB lithium ion rechargeable battery along with a host of features, the 2780R makes for one of the most intriguing headlamps. The easy grip dial provides selection of the Main LED which illuminates everything in front with a beam distance of 139 meters, the Downcast LED illuminates everything below in a wide diffused pattern providing safe pathways, illuminated reading spaces and allowing for non-blinding face to face conversations, both beams combined, or a helpful flashing mode round out the forward light outputs. The easy grip dial also incorporates a push to select High / Medium / Low settings. Additional features offered in the 2780R are a unique rear mounted battery pack that provides full time battery level indication, charging levels and a rear mounted red LED safety light.

The Peli™ 2780R Rechargeable LED Headlamp: The very best in hands free lighting.

- Downcast LED Technology
- Includes 3 interchangeable Covers (Black, White, Photoluminescent)
- 676 High Intensity Lumens
- USB Lithium Ion Rechargeable
- Rear Mounted Red LED
- Pivoting Head
- Comfortable Cloth Strap
- Includes Full Time Battery Status Indication



DIMENSIONS

Length 3.00" (7.6 cm)

MATERIALS

Body Polycarbonate (PC)
O-Ring Gasket
Lens Polycarbonate (PC)
Shroud Polycarbonate (PC)

COLOURS

■ Black / White / Photoluminescent

LIGHT SPECS

Lamp Type LED
Lamp Secondary Type LED

POWER

Battery Size 18650
Battery Type Lithium-Ion
Battery Quantity 1
Batteries Included yes
Rechargeable yes

Charge Time 6 hrs
Battery Level Indicator 3 Blue LEDs
Volts 3.7v

WEIGHT






Weight With Batteries 7.3 oz (207 gr)
Weight Without Batteries 5.6 oz (159 gr)

SWITCH

Switch Type Rotary / Push Button
Light Modes High / Medium / Low / Downcast / Spot / Flashing

OTHER

Minimum Pack 1
Package Code C

| FL1 STANDARD | FLOOD HIGH | FLOOD MED | FLOOD LOW | SPOT / FLOOD HIGH | SPOT / FLOOD MED | SPOT / FLOOD LOW | SPOT HIGH | SPOT MED | SPOT LOW |
|---|------------|------------|-----------|-------------------|------------------|------------------|------------|------------|-----------|
|  | 397 LUMENS | 185 LUMENS | 92 LUMENS | 676 LUMENS | 252 LUMENS | 118 LUMENS | 414 LUMENS | 187 LUMENS | 93 LUMENS |
|  | 4h 30mins | 6h 0mins | 13h 0mins | 2h 30mins | 4h 15mins | 10h 0mins | 4h 30mins | 5h 45mins | 13h 0mins |
|  | 86m | 58m | 40m | 139m | 78m | 53m | 139m | 93m | 65m |
|  | 1858cd | 836cd | 403cd | 4060cd | 1540cd | 695cd | 4824cd | 2158cd | 1051cd |
|  | IPX7 | | | | | | | | |

ACCESSORIES



2389
Replacement Battery

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 03-24-26