

1930Z0

I 1 ™

Same features as L1[™] 1930 LED with static-dissipation materials body. Being certified to ATEX safe for use in high-risk hazardous locations, Zone 0 (Category 1) areas, L1[™] 1930Z0 LED is ideal for professionals who work in chemical, pharmaceutical, power, oil and gas, and fire rescue industries.



DIMENSIONS

Length 2.64" (6.7 cm)

MATERIALS

Body Anti-static Impact Modified PC/PBT

O-Ring Ethylene Propylene Lens Polycarbonate (PC)

Shroud Anti-static Impact Modified PC/PBT

Contact Spring Retainer Phosphore Bronze

COLOURS

Gray

LIGHT SPECS

Lamp Type LED

POWER

Battery SizeLR 44Battery TypeAlkalineBattery Quantity4Batteries IncludedyesVolts6.0v

WEIGHT

Weight With Batteries 0.9 oz (26 gr)
Weight Without
Batteries 0.6 oz (17 gr)
Packaged Weight 0.8 oz (23 gr)

SWITCH


Switch Type Push Button Tail
Light Modes On / Off

CERTIFICATIONS

ATEX Zone 0

OTHER

Minimum Pack12MilitaryyesPackage CodeC



Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 12-05-25