



## PR2012-01/18/01

ProRack™  
6U

Peli™ ProRack™ cases are lightweight, space-efficient, front and rear opening transport container (not a shock mounted/cushioned rackmount system) for field ruggedized equipment.

- Designed for equipment up to 75 lbs
- Equipment typically will have 80-120 G fragility
- Rugged 18" deep cases w/ aircraft aluminum frame suspended on plastic fins to protect your gear from direct impact transmission
- Often used for field-deployed amplifiers and electronic, medical or testing equipment components



### DIMENSIONS

---

<b>Exterior (L×W×D)</b>	22.00 x 22.40" x 14.80 (55.9 x 56.9 x 37.6 cm)
<b>Rack Depth</b>	18.00" (45.7 cm)
<b>Interior Lid Depth</b>	1.81" (4.6 cm)
<b>Interior Back Lid Depth</b>	1.81" (4.6 cm)

### MATERIALS

---

### COLOURS

---

■ Black - 032 Fed Std  
27040

### WEIGHT

---

<b>Weight</b>	23.90 lbs (10.8 kg)
---------------	---------------------

---

#### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

Document created on 11-21-24