



SUPER-V-SERIES-14U

Super V

14U

- SUPER V-SERIES 14U, 2128-02/29/05W
- Fixed square hole frame for universal equipment fit
- 2" Front Lid, 5" Rear Lid
- Anti-reflective black hardware
- Coupling catches for secure stacking
- Available in 3U, 4U, 5U, 7U, 9U, 11U, and 14U
- Weight ranges for 7U - 14U = 100-170lbs per case
- Molded in rear edge casters with handles on the lid for ease of movement
- Comfort Grip plastic handles
- Metric M6 clip nuts for more flexibility in mounting equipment
- Engineered to provide secure transport for rack mountable electronics
- Equipment payload weight ranges for 3U - 5U = 80-100 lbs. (36-45 kg) per case
- Lid hangers for lid storage while in use
- Sealed gasket and PRV keeps container watertight and eliminates over pressurization
- REACH and RoHS compliant



DIMENSIONS

| | |
|--------------------------------|--|
| Exterior (LxWxD) | 38.50 x 28.30" x 30.60 (97.8 x 71.9 x 77.7 cm) |
| Rack Height | 24.50" (62.2 cm) |
| Rack Depth | 24.00" (61 cm) |
| Interior Lid Depth | 2.20" (5.6 cm) |
| Interior Back Lid Depth | 5.20" (13.2 cm) |

MATERIALS

| | |
|-------------------|---|
| Body | RotoMolded Polyethylene |
| O-Ring | Silicone Sponge |
| Purge Body | Aluminum |
| Hardware | Stainless Steel (Black Oxide) / RoHS Nickel Black |
| Frame | Steel (Clear Coated) |

COLOURS

■ Black

WEIGHT

| | |
|---------------|---------------------|
| Weight | 74.00 lbs (33.6 kg) |
|---------------|---------------------|

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 07-17-24