



# SUPER-V-SERIES-14U

## Super V

14U

- SUPER V-SERIES 14U, 2128-02/29/05W
- Fixed square hole frame for universal equipment fit
- 2" Front Lid, 5" Rear Lid
- Anti-reflective black hardware
- Coupling catches for secure stacking
- Available in 3U, 4U, 5U, 7U, 9U, 11U, and 14U
- Weight ranges for 7U - 14U = 100-170lbs per case
- Molded in rear edge casters with handles on the lid for ease of movement
- Comfort Grip plastic handles
- Metric M6 clip nuts for more flexibility in mounting equipment
- Engineered to provide secure transport for rack mountable electronics
- Equipment payload weight ranges for 3U - 5U = 80-100 lbs. (36-45 kg) per case
- Lid hangers for lid storage while in use
- Sealed gasket and PRV keeps container watertight and eliminates over pressurization
- REACH and RoHS compliant



### DIMENSIONS

<b>Exterior (LxWxD)</b>	38.50 x 28.30" x 30.60 (97.8 x 71.9 x 77.7 cm)
<b>Rack Height</b>	24.50" (62.2 cm)
<b>Rack Depth</b>	24.00" (61 cm)
<b>Interior Lid Depth</b>	2.20" (5.6 cm)
<b>Interior Back Lid Depth</b>	5.20" (13.2 cm)

### MATERIALS

<b>Body</b>	RotoMolded Polyethylene
<b>O-Ring</b>	Silicone Sponge
<b>Purge Body</b>	Aluminum
<b>Hardware</b>	Stainless Steel (Black Oxide) / RoHS Nickel Black
<b>Frame</b>	Steel (Clear Coated)

### COLOURS

■ Black

### WEIGHT

<b>Weight</b>	74.00 lbs (33.6 kg)
---------------	---------------------

#### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

Document created on 11-24-24