



EURO-V-4U-L

Euro-V

4U

The Euro-V Rack Case is a smooth-finished, rotomoulded case featuring a 19" wide EIA standard rack with depths of 610 mm and 760 mm, designed to support metric-mounted equipment via an industry-standard square hole pattern (M6).

Lightweight yet robust, the Peli Euro-V Rack Case offers medium-duty protection in a streamlined format. Built for rapid deployment, it incorporates wall-mounted cylindrical shock mounts that isolate sensitive equipment from shock and vibration. Its interstackable design ensures compatibility with Super-V and BlackBox rack cases, enabling seamless integration across mixed fleets.

Manufactured in Germany to reduce lead times, the Euro-V is available in nine sizes (4U to 10U), all with moulded-in stacking ribs, edge casters, and a steel rack frame – pre-configured for fast, dependable field use.

Euro-V Rack Cases are ideal for mission-critical applications where reliable protection in a lighter, more compact design is essential. When precision equipment needs to arrive intact and on schedule, trust the Peli Euro-V Rack Case to deliver.



- Made in Germany for faster delivery and reduced lead times
- Optimised for Metric Equipment – Features a steel rack with an industry-standard square hole pattern (M6 clip nuts available).
- Durable & Shock-Resistant – Equipped with cylindrical shock mounts for maximum protection.
- Varied Depths – Available in 610mm (24") and 762mm (30") depths.
- Enhanced Mobility – Designed with 8 black plastic handles and edge casters for easy transport.

DIMENSIONS

| | |
|--------------------------------|---|
| Exterior (LxWxD) | 45.00 x 24.68" x 13.60 (114.3 x 62.7 x 34.5 cm) |
| Rack Height | 19.00" (48.3 cm) |
| Rack Depth | 30.00" (76.2 cm) |
| Interior Lid Depth | 2.20" (5.6 cm) |
| Interior Back Lid Depth | 5.20" (13.2 cm) |

MATERIALS

COLOURS

■ Black

WEIGHT

| | |
|---------------|---------------------|
| Weight | 51.80 lbs (23.5 kg) |
|---------------|---------------------|

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

info@peli.com • www.peli.com

