



1505

Air

The 1505 Air case is a versatile, shallow attaché-style case with built-in functionality to support panel mounting in the lid and base. Protect laptops and sensitive electronics or leverage the out-of-the-box panel mounting capability to engineer your own mobile communications system, cradlepoint, or battery charging station. Whether you're a construction professional transporting your laptop to the site, a law enforcement team relying on a cradlepoint to maintain communications, or prototyping a new medical device, the 1505 Air case delivers the ultimate combination of durability, portability, and versatility.

- Integrated bezel system for panel mounting
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified
- Super-light proprietary HPX²™ Polymer - up to 40% lighter
- Press and Pull™ Latches
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Fold down overmolded handle
- Waterproof O-ring seal
- Stainless steel padlock protectors
- Limited Lifetime Warranty



CONFIGURATIONS



1505
Standard



1505NF
No Foam



1505WF
With Foam



1505TP
With TrekPak Divider System

DIMENSIONS

Interior (LxWxD)	18.29 x 13.26" x 5.46 (46.5 x 33.7 x 13.9 cm)
Exterior (LxWxD)	20.22 x 16.38" x 6.10 (51.4 x 41.6 x 15.5 cm)
Lid Depth	1.93" (4.9 cm)
Bottom Depth	3.53" (9 cm)
Total Depth	5.46" (13.9 cm)
Int Volume	0.77 ft ³ (0.022 m ³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Proprietary Polypropylene Blend
Latch	ABS
O-Ring	EPDM
Pins	Stainless Steel

Foam	Polyurethane
Purge Body	ABS
Purge Vent	Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven
Handle	Polypropylene and Thermoplastic Rubber Side Handle

COLOURS

■ Black

WEIGHT

Weight With Foam	6.55 lbs (3 kg)
Weight Empty	5.80 lbs (2.6 kg)
Buoyancy	54.00 lbs (24.5 kg)

TEMPERATURE

Minimum Temperature	0°F (-17.8 °C)
Maximum Temperature	140°F (60 °C)

ACCESSORIES



1505FS
3 pc. Replacement Foam Set



1472
Shoulder Strap

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 08-28-25