



# 1630

## Protector

Transport Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **4 strong polyurethane wheels with stainless steel bearings (wheel diameter is 5.3cm)**
- **Watertight, crushproof, and dustproof**
- 3 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Easy open double-throw latches
- Fold down handles
- Note: Please consult a sales specialist for more details.
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Reinforced corners
- Retractable extension trolley handle
- Stackable
- Stainless steel padlock protectors
- Peli's legendary lifetime guarantee\*\*
- \* Where applicable by law



### CONFIGURATIONS



**1630**  
Standard



**1634**  
With Padded Dividers



**1630NF**  
No Foam



**1630WF**  
With Foam

### DIMENSIONS

<b>Interior (LxWxD)</b>	27.70 x 20.98" x 15.50 (70.4 x 53.3 x 39.4 cm)
<b>Exterior (LxWxD)</b>	31.28 x 24.21" x 17.48 (79.5 x 61.5 x 44.4 cm)
<b>Lid Depth</b>	3.25" (8.3 cm)
<b>Bottom Depth</b>	12.14" (30.8 cm)
<b>Total Depth</b>	15.39" (39.1 cm)
<b>Int Volume</b>	5.21 ft <sup>3</sup> (0.148 m <sup>3</sup> )
<b>Padlock Hole Diameter</b>	0.31" (0.8 cm)

### MATERIALS

<b>Body</b>	Polypropylene
-------------	---------------

<b>Latch</b>	ABS
<b>O-Ring</b>	Polymer
<b>Pins</b>	Stainless Steel
<b>Foam</b>	1.3 lb Polyurethane
<b>Purge Body</b>	ABS
<b>Purge Vent</b>	3 Micron Hydrophobic Non-Woven

## COLOURS

 Black	 Desert Tan	 OD Green
---	--	--

## WEIGHT

<b>Weight With Foam</b>	36.00 lbs (16.33 kg)
<b>Weight Empty</b>	31.00 lbs (14.06 kg)
<b>Buoyancy</b>	350.00 lbs (158.76 kg)
<b>Master Pack Weight</b>	42.00 lbs (19.05 kg)

## TEMPERATURE

<b>Minimum Temperature</b>	-40°F (-40 °C)
<b>Maximum Temperature</b>	190°F (87.8 °C)

## CERTIFICATIONS

**IP67**  
**Def Stan 81-41**

## OTHER

<b>Wheels</b>	4
<b>Extendable Handle</b>	yes
<b>Master Pack</b>	1
<b>Nameplate</b>	yes
<b>Reduced Area</b>	yes

## ACCESSORIES



**1631**  
5 pc. Replacement Foam Set



**1633**  
Replacement O-ring



**1635**  
Padded Divider Set



**1639**  
Lid Organizer



**1630DC**  
Document Container  
Accessory



**1507QM**  
Quick Mounts - set of 4



**1506TSA**  
TSA Lock



**1500D**  
Desiccant Silica Gel

---

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 04-28-26*