



1460EMS

Protector

EMS Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- Also available without EMS Organizer and Dividers
- **Lockable compartment for controlled substances**
- **Specifically designed in conjunction with Fire department and EMS personnel**
- **Top lid opens up to 180° for on-the-field anti-roll stability when open**
- Adjustable tray dividers allow for easy customization
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Each tray has an overall internal dimension of: 17" x 7.65" x 1.36" (43.18 x 19.43 x 3.45cm) LxWxD
- Easy open double-throw latches
- O-ring seal for dust and water resistant seal (IP66)
- Open cell core with solid wall design - strong, light weight
- Sharps storage bracket included
- Stainless steel hardware and padlock protectors
- *Sharps container not included
- Peli's legendary lifetime guarantee**
- * Where applicable by law



DIMENSIONS

Interior (LxWxD)	18.54 x 9.92" x 10.92 (47.1 x 25.2 x 27.7 cm)
Exterior (LxWxD)	20.85 x 12.73" x 12.75 (53 x 32.3 x 32.4 cm)
Lid Depth	4.91" (12.5 cm)
Bottom Depth	6.01" (15.3 cm)
Total Depth	10.92" (27.7 cm)
Int Volume	1.16 ft ³ (0.033 m ³)
Padlock Hole Diameter	5/16" (12.7 cm)

MATERIALS

Body	Polypropylene
Latch	EXL
O-Ring	Polymer
Pins	Stainless Steel
Foam	Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

 Orange

WEIGHT

Weight 18.20 lbs (8.3 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C)
Maximum Temperature 210°F (98.9 °C)

CERTIFICATIONS

IP66
NTOA Approved

OTHER

Military yes

ACCESSORIES



1463
Replacement O-ring



1466
Tray System for 1460EMS



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 11-23-24