

1460EMS

Protector

EMS Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- Also available without EMS Organizer and Dividers
- Lockable compartment for controlled substances
- Specifically designed in conjunction with Fire department and EMS personnel
- Top lid opens up to 180° for on-the-field anti-roll stability when open
- Adjustable tray dividers allow for easy customization
- Automatic pressure equalization valve balances interior pressure, keeps water out
- \bullet Each tray has an overall internal dimension of: 17" x 7.65" x 1.36" (43.18 x 19.43 x 3.45cm) LxWxD
- · Easy open double-throw latches
- O-ring seal for dust and water resistant seal (IP66)
- Open cell core with solid wall design strong, light weight
- Sharps storage bracket included
- Stainless steel hardware and padlock protectors
- *Sharps container not included
- Peli's legendary lifetime guarantee**
- * Where applicable by law



DIMENSIONS

Interior (L×W×D) 18.54 x 9.92" x 10.92 (47.1 x 25.2 x 27.7 cm) Exterior (L×W×D) 20.85 x 12.73" x 12.75 (53 x 32.3 x 32.4 cm)

 Lid Depth
 4.91" (12.5 cm)

 Bottom Depth
 6.01" (15.3 cm)

 Total Depth
 10.92" (27.7 cm)

 Int Volume
 1.16 ft³ (0.033 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

MATERIALS

Body Polypropylene

LatchEXLO-RingPolymerPinsStainless SteelFoamPolyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS

Orange

WEIGHT

Weight 18.20 lbs (8.3 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

CERTIFICATIONS

IP66

NTOA Approved

OTHER

Military

yes

ACCESSORIES



1463 Replacement O-ring



1466 Tray System for 1460EMS



1506TSA TSA Lock



1500D Desiccant Silica Gel

Peli

Document created on 12-11-25