



1520EU Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

These tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **Watertight, crushproof, and dustproof**
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Pick N Pluck™ with convoluted lid foam
- Stainless steel hardware and padlock protectors
- Made in Germany
- Peli's legendary lifetime guarantee**
- * Where applicable by law



CONFIGURATIONS



1520EU
Standard



1524
With Padded Dividers



1520NF
No Foam



1520WF
With Foam

DIMENSIONS

| | |
|------------------------------|---|
| Interior (L×W×D) | 17.68 x 12.53" x 6.73 (44.9 x 31.8 x 17.1 cm) |
| Exterior (L×W×D) | 19.65 x 15.49" x 7.53 (49.9 x 39.3 x 19.1 cm) |
| Lid Depth | 1.79" (4.5 cm) |
| Bottom Depth | 4.93" (12.5 cm) |
| Total Depth | 6.72" (17.1 cm) |
| Int Volume | 0.86 ft ³ (0.024 m ³) |
| Padlock Hole Diameter | 5/16" (12.7 cm) |

MATERIALS

| | |
|---------------|---------------------|
| Body | Polypropylene |
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |

Purge Body ABS
Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS

| | | | |
|--|--|--|--|
|  Black |  Desert Tan |  Orange |  OD Green |
|  Silver |  Yellow | | |

WEIGHT

| | |
|---------------------------|---------------------|
| Weight With Foam | 9.35 lbs (4.2 kg) |
| Weight Empty | 8.29 lbs (3.8 kg) |
| Buoyancy | 63.00 lbs (28.6 kg) |
| Master Pack Weight | 23.30 lbs (10.6 kg) |

TEMPERATURE

| | |
|----------------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 210°F (98.9 °C) |

CERTIFICATIONS

IP67
MIL C-4150J
Def Stan 81-41

OTHER

| | |
|--------------------|-----|
| Master Pack | 2 |
| Nameplate | yes |
| Military | yes |

ACCESSORIES



1508
Photographer's Lid Organizer



1509
Lid Organizer



1521
3 pc. Replacement Foam Set



1523
Replacement O-ring



1525
Padded Divider Set



1520TPKIT
TrekPak Case Divider Kit



1507
Quick Mounts - set of 4



1506TSA
TSA Lock



1500D
Desiccant Silica Gel



1520PF
Special Application Panel Frame



1520TPDIV
Extra TrekPak Dividers

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 03-31-25