



iM2600 Storm

The Peli™ Storm Case™ has the same legendary DNA as our Peli Protector Case, with one primary difference: A unique Press and Pull latch that locks automatically, but open with a light touch. Guaranteed for life, the Peli Storm case is made in the USA and engineered using the finest components.

- **Watertight, crushproof, and dustproof**
- Two Press & Pull Latches
- Two Padlockable Hasps
- Double-layered, Soft-grip Handle
- Vortex™ Valve
- Powerful Hinges
- Lightweight Strong HPX® Resin



CONFIGURATIONS



iM2600
Standard



iM2600-X0000
No Foam



iM2600-X0002
With Padded Dividers



iM2600-X0001
With Foam

DIMENSIONS

Interior (LxWxD)	20.00 x 14.00" x 7.70 (50.8 x 35.6 x 19.6 cm)
Exterior (LxWxD)	21.20 x 16.00" x 8.30 (53.8 x 40.6 x 21.1 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	5.70" (14.5 cm)
Total Depth	7.7" (19.6 cm)
Int Volume	1.25 ft ³ (0.035 m ³)
Padlock Hole Diameter	1/4" (2.5 cm)

MATERIALS

Body	Injection Molded HPX™ high performance resin
Latch	Valox - Polybutylene Terephthalate (PBT)
Latch (Alt)	Xenoy - Polyester/Polycarbonate blend
O-Ring	EPDM
Pins	Stainless Steel
Pins (Alt)	Aluminum
Foam	1.3/1.35 polyester
Purge Body	Valox - Polybutylene Terephthalate (PBT)
Purge Body (Alt)	Xenoy - Polyester/Polycarbonate blend
Purge Vent	Gortex membrane

COLOURS

■ Black

■ OD Green

■ Yellow

WEIGHT

Weight With Foam	11.60 lbs (5.3 kg)
Weight Empty	8.50 lbs (3.9 kg)
Buoyancy	79.81 lbs (36.2 kg)
Master Pack Weight	24.20 lbs (11 kg)

TEMPERATURE

Minimum Temperature	-20°F (-28.9 °C)
Maximum Temperature	140°F (60 °C)

CERTIFICATIONS

IP67

OTHER

Master Pack	2
Military	yes

ACCESSORIES



iM26XX-LIDORG
Lid Organizer



iM2600-FOAM
5 pc. Replacement Foam Set



iM-STRAP-S-VER2
Padded Shoulder Strap



iM-LIDSTAY
Lid Stay




iM2600-M4-BEZEL-L
Lid Bezel (Metric)



iM2600-MBEZ-B
Base Bezel (Metric)



iM26XX-UTILITYORG
Utility Organizer



iM2600-TREK
TrekPak Case Divider Kit



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 08-18-22