



1975Z0

Stay trim and powerful in the danger zone. With ATEX Zone 0 (Category 1) certification, 117 blinding bright lumens, and a true penlight size and shape, the Peli™ 1975Z0 torch is the slimmest and brightest safety approved penlight.

Engineered with an aluminum core and anti-static impact modified PC/PBT, the Peli™ 1975Z0 penlight can survive tough work environments, yet is slim enough to snap into the available helmet mount or hold with your teeth.

The 1975Z0 activates with a click of the tail switch or light pressure for momentary use.

The Peli™ 1975Z0 penlight: Make danger your pen pal.

- 2 AAA Batteries
- Safety Certified ATEX Zone 0 (Category 1)
- Slim and Tough Design
- Full / Momentary Activation Tail Switch
- 117 Lumens
- Helmet Mount (sold separately)




DIMENSIONS

| | |
|---------------|-----------------|
| Length | 5.75" (14.6 cm) |
|---------------|-----------------|

MATERIALS

| | |
|---------------|------------------------------------|
| Body | Anti-static Impact Modified PC/PBT |
| O-Ring | NBR |
| Lens | PC |
| Shroud | Anti-static Impact Modified PC/PBT |
| Clip | Anti-static Impact Modified PC/PBT |

COLOURS

 High Visibility Yellow

LIGHT SPECS

| | |
|------------------|-----|
| Lamp Type | LED |
|------------------|-----|

POWER

| | |
|---------------------------|----------|
| Battery Size | AAA |
| Battery Type | Alkaline |
| Battery Quantity | 2 |
| Batteries Included | yes |
| Volts | 3.0v |

WEIGHT






| | |
|---------------------------------|----------------|
| Weight With Batteries | 1.9 oz (54 gr) |
| Weight Without Batteries | 1.0 oz (28 gr) |

SWITCH

Switch Type Momentary Push Button
Light Modes High

CERTIFICATIONS

ATEX Zone 0

| FL1 STANDARD | HIGH |
|---|---------------|
|  | 117 LUMENS |
|  | 2h 15mins |
|  | 24m |
|  | 141cd |
|  | IP68 |

ACCESSORIES



1975H
Helmet Light Holder

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

