



AL5632-0404FT

For over 65 years Peli's roto-molded cases have been relied upon for an unmatched range of engineered solutions for the Military and Medical, Telecommunications and High Tech industries. Peli offers over 350 case sizes with unlimited case configurations using standard case options. Either build your own case or our engineers will customize a solution specific to your performance requirements.

Our roto molded cases pass MIL-STD 810D and E, MIL-STD 810E MIL-STD-210C, ASTM E96; FED-STD-101 and ATA 300 testing.

This level of performance ensures your equipment is safe from any unforeseen elements when deploying, transporting or storing your most valuable assets.

- Hardware attaches to molded-in metal inserts to provide pull-out strength and load spreading so hardware never fails.
- Molded-in ribs and corrugations offer case strength for secure and heavy weight stacking capacity
- Recessed hardware, with its engineered shoulder geometry, reduces shear forces that prevents lid separation after impact and controls pressure on the gasket to maintain a weatherproof seal
- Усиленные углы и края для дополнительной защиты от удара
- Литые ребра жесткости и другой рельеф помогает закрепить контейнеры при штабелировании, придает вертикальную силу и дополнительную защиту
- Цельная конструкция, отлитая из легкого высокопрочного полиэтилена



РАЗМЕРЫ

ИНТЕРЬЕР	56.05 x 32.42" x 8.31 (142.4 x 82.3 x 21.1 cm)
ВНЕШНИЙ ВИД	59.06 x 35.43" x 14.00 (150 x 90 x 35.6 cm)
глубина крышки	3.88" (9.9 cm)
глубина дна	3.98" (10.1 cm)
общая глубина	7.86" (20 cm)
внутренний объем	8.74 ft ³ (0.247 m ³)

МАТЕРИАЛЫ

корпус	RotoMolded Polyethylene
замок-защелка	Steel (Nickel-black Plated)
уплотнительное кольцо	Silicone Sponge
вспененный материал	No Foam, empty case standard Optional PE and PU, 1 and 2 lb. options filled and lined
корпус спускового клапана	Aluminum
ручка	Heavy Duty Injection Molded Standard
Фурнитура	Yellow Carbon Steel Standard

ЦВЕТА

■ Gray - 133 Fed Std
26270

ВЕС

масса 55.59 lbs (25.2 kg)

ТЕМПЕРАТУРА

минимальная температура -20°F (-28.9 °C)

максимальная температура 140°F (60 °C)

ДРУГИЕ

Военные учреждения да

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 07-17-24