

# 1637 Air

Meet the lightest premium Protector™ case on the planet. Up to 40% lighter than other polymer cases.

Peli<sup>™</sup> Air cases are the first in a series of remarkable innovations

engineered by Peli, the pioneers of protective cases. For over 40 years Peli has designed and crafted the most influential protective cases in the world, and we're just getting started.

With the launch of the Peli<sup>™</sup> Air line of cases, we're redefining the future of protection with a remarkable union of light and tough.

• Automatic pressure equalization valve - balances interior pressure, keeps water out

- Fold down over-molded handle
- Retractable extension trolley handle
- Stainless steel padlock protectors
- Business card holder
- Quiet rolling stainless-steel bearing wheels
- Press and Pull™ Latches
  Limited Lifetime Warranty
- Super-light proprietary HPX<sup>2™</sup> Polymer up to 40% lighter
- Waterproof O-ring seal
- User-customizable Pick N Pluck<sup>™</sup> foam
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified



# CONFIGURATIONS



1637 Standard



1637NF

No Foam



1637WD With Padded Dividers



1637WF With Foam



WINF-12B 12-Bottle Wine

### DIMENSIONS

Interior (L×W×D)	23.43 x 17.55" x 13.25 (59.5 x 44.6 x 33.7 cm)		
Exterior (L×W×D)	26.61 x 20.65" x 14.87 (67.6 x 52.5 x 37.8 cm)		
Lid Depth	2.00" (5.1 cm)		
Bottom Depth	11.20" (28.4 cm)		
Total Depth	al Depth 13.2" (33.5 cm)		
Int Volume	3.15 ft <sup>3</sup> (0.089 m <sup>3</sup> )		
Padlock Hole Diameter	0.31" (0.8 cm)		

#### MATERIALS

Proprietary Polypropylene Blend		
ABS		
EPDM		
ABS		
Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven		

# COLOURS

Black	Orange	Silver	Yellow
WEIGHT			
Weight With Foam	19.40 lbs (8.8 kg)		
Weight Empty	15.20 lbs (6.9 kg)		
Buoyancy	209.00 lbs (94.8 kg)		
TEMPERATURE			
Minimum Temperature	0°F (-17.8 °C)		
Maximum Temperature	140°F (60 °C)		
· · · · · · · · · · · · · · · · · · ·			

### OTHER

Wheels

2

## ACCESSORIES



Peli c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 08-07-25