

# 2460Z1

# StealthLite™

The rechargeable version of the StealthLite™ 2410 LED. The StealthLite™ Rechargeable 2460Z1 LED uses the 2469P NiMH battery and comes with the charger base unit cat # 2480F that can be installed at home or work using the 220V transformer cat # 2468Z1. Certified to ATEX Zone 1 (Category 2). Note, this charger base does not work on 12v systems.



# **DIMENSIONS**

**Length** 7.00" (17.8 cm)

#### **MATERIALS**

**Body** Anti-static Impact Modified PC/PBT

**O-Ring** Ethylene Propylene **Lens** Polycarbonate (PC)

**Shroud** Anti-static Impact Modified PC/PBT **Contact Spring Retainer** Stainless Steel / Phosphore Bronze

### **COLOURS**

High Visibility Yellow

#### LIGHT SPECS

Lamp Type LED

# **POWER**

Battery Size AA
Battery Type NiMH
Battery Quantity 4
Batteries Included yes
Rechargeable yes
Charge Time 8 hrs
Volts 4.8v

### WEIGHT

Weight With Batteries 7.8 oz (221 gr)
Weight Without
Batteries 4.4 oz (125 gr)
Packaged Weight 1.4 oz (40 gr)

### **SWITCH**

**Switch Type** One-handed Safety Switch

**Light Modes** On / Off

# ATEX Zone 1

# OTHER

Minimum Pack1MilitaryyesPackage CodeC

| FL1 STANDARD | HIGH          |
|--------------|---------------|
|              | 181<br>LUMENS |
| $\Theta$     | 5h 0mins      |
|              | 181m          |
|              | 8235cd        |
| The second   | IPX7          |

# **ACCESSORIES**



**0770** Helmet Light Holder



**2480F** Deck/Dash Charger Base Unit



**2469P** Replacement Battery

 $\underline{\mathsf{info@peli.com}} \bullet \underline{\mathsf{www.peli.com}}$ 

Document created on 11-08-25