



2460Z1 StealthLite™

The rechargeable version of the StealthLite™ 2410 LED. The StealthLite™ Rechargeable 2460Z1 LED uses the 2469P NiMH battery and comes with the charger base unit cat # 2480F that can be installed at home or work using the 220V transformer cat # 2468Z1. Certified to ATEX Zone 1 (Category 2). Note, this charger base does not work on 12v systems.



DIMENSIONS

| | |
|---------------|-----------------|
| Length | 7.00" (17.8 cm) |
|---------------|-----------------|

MATERIALS

| | |
|--------------------------------|------------------------------------|
| Body | Anti-static Impact Modified PC/PBT |
| O-Ring | Ethylene Propylene |
| Lens | Polycarbonate (PC) |
| Shroud | Anti-static Impact Modified PC/PBT |
| Contact Spring Retainer | Stainless Steel / Phosphore Bronze |

COLOURS

 High Visibility Yellow

LIGHT SPECS

| | |
|------------------|-----|
| Lamp Type | LED |
|------------------|-----|

POWER

| | |
|---------------------------|-------|
| Battery Size | AA |
| Battery Type | NiMH |
| Battery Quantity | 4 |
| Batteries Included | yes |
| Rechargeable | yes |
| Charge Time | 8 hrs |
| Volts | 4.8v |

WEIGHT

| | |
|---------------------------------|-----------------|
| Weight With Batteries | 7.8 oz (221 gr) |
| Weight Without Batteries | 4.4 oz (125 gr) |
| Packaged Weight | 1.4 oz (40 gr) |

SWITCH






| | |
|--------------------|--------------------------|
| Switch Type | One-handed Safety Switch |
| Light Modes | On / Off |

CERTIFICATIONS

ATEX Zone 1

OTHER

Minimum Pack 1
Military yes
Package Code C

| FL1 STANDARD | HIGH |
|---|---------------|
|  | 181 LUMENS |
|  | 5h 0mins |
|  | 181m |
|  | 8235cd |
|  | IPX7 |

ACCESSORIES



0770
Helmet Light Holder



2480F
Deck/Dash Charger Base Unit



2469P
Replacement Battery

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

info@peli.com • www.peli.com

Document created on 06-05-26