

# 1606

#### Air

Peli understands that finding the right protection, with the perfect fit for your gear, is a priority. Peli™ Air began with long protection and quickly grew to offer you deep protection. The time has come to combine those two in order to create Peli's new Long/Deep Series. Gone are the days of dangerously forcing your equipment into the wrong size case or leaving it unprotected with no other options. With Peli's Long/Deep series, we've created the missing link so that no matter the demands of your gear, Peli has you covered.

- Automatic pressure equalization valve balances interior pressure, keeps water out
- Fold down over-molded handle
- Retractable extension trolley handle
- Stainless steel padlock protectors
- · Business card holder
- Quiet rolling stainless-steel bearing wheels
- Press and Pull™ Latches
- · Limited Lifetime Warranty
- Super-light proprietary HPX<sup>2™</sup> Polymer up to 40% lighter
- · Waterproof O-ring seal
- User-customizable Pick N Pluck™ foam
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified



## **CONFIGURATIONS**



**1606** Standard



**1606WF** With Foam



**1606NF** No Foam

#### **DIMENSIONS**

 Interior (L×W×D)
 24.54 x 12.30" x 10.22 (62.3 x 31.2 x 26 cm)

 Exterior (L×W×D)
 27.42 x 15.13" x 11.83 (69.6 x 38.4 x 30 cm)

 Lid Depth
 2.00" (5.1 cm)

 Bottom Depth
 8.22" (20.9 cm)

 Total Depth
 10.22" (26 cm)

 Int Volume
 1.79 ft³ (0.051 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

#### **MATERIALS**

**Body** Proprietary Polypropylene Blend

Latch ABS O-Ring EPDM

Purge Body ABS

Purge Vent Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

# **COLOURS**

Black

### WEIGHT

 Weight With Foam
 14.67 lbs (6.7 kg)

 Weight Empty
 12.45 lbs (5.6 kg)

 Buoyancy
 123.70 lbs (56.1 kg)

# **TEMPERATURE**

**Minimum Temperature** 0°F (-17.8 °C) **Maximum Temperature** 140°F (60 °C)

# **ACCESSORIES**



**1606AirFS** 8 pc. Replacement Foam Set

#### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 07-26-25