

0350

Protector

Cube Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- · Large 2-person fold down handles
- Watertight, crushproof, and dustproof
- 3 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps water out
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors
- Peli's legendary lifetime guarantee**
- * Where applicable by law



CONFIGURATIONS



0350 Standard



0354With Padded Dividers



0350NF No Foam



0350WF With Foam

DIMENSIONS

Interior (L×W×D) 20.00 x 20.00" x 20.00 (50.8 x 50.8 x 50.8 cm) Exterior (L×W×D) 22.50 x 22.43" x 21.25 (57.2 x 57 x 54 cm)

 Lid Depth
 5.00" (12.7 cm)

 Bottom Depth
 15.00" (38.1 cm)

 Total Depth
 20" (50.8 cm)

 Int Volume
 4.63 ft³ (0.131 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

MATERIALS

Body Polypropylene

Latch ABS O-Ring Polymer

PinsStainless SteelFoam1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS



WEIGHT

 Weight With Foam
 32.01 lbs (14.5 kg)

 Weight Empty
 25.99 lbs (11.8 kg)

 Buoyancy
 268.96 lbs (122 kg)

 Master Pack Weight
 33.89 lbs (15.4 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C)
Maximum Temperature 190°F (87.8 °C)

CERTIFICATIONS

IP67

Def Stan 81-41

OTHER

Master Pack1NameplateyesReduced AreayesMilitaryyes

ACCESSORIES



7 pc. Replacement Foam Set



0353 Replacement O-ring



0355 Padded Divider Set



0357 Cube Case Mobility Package



1507 Quick Mounts - set of 4



1506TSA TSA Lock



1500D Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 11-03-25