

0350 Protector Cube Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

• Large 2-person fold down handles

- Watertight, crushproof, and dustproof
- 3 level Pick N Pluck $^{\rm m}$ with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps
- water out
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Stainless steel hardware and padlock protectors
- Peli's legendary lifetime guarantee**
- * Where applicable by law

CONFIGURATIONS



0350 Standard



0354 With Padded Dividers



0350NF No Foam



0350WF With Foam

DIMENSIONS

Interior (L×W×D)	20.00 x 20.00" x 20.00 (50.8 x 50.8 x 50.8 cm)
Exterior (L×W×D)	22.50 x 22.43" x 21.25 (57.2 x 57 x 54 cm)
Lid Depth	5.00" (12.7 cm)
Bottom Depth	15.00" (38.1 cm)
Total Depth	20" (50.8 cm)
Int Volume	4.63 ft ³ (0.131 m ³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer

Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLOURS

Black

WEIGHT

Weight With Foam	32.01 lbs (14.5 kg)
Weight Empty	25.99 lbs (11.8 kg)
Buoyancy	268.96 lbs (122 kg)
Master Pack Weight	33.89 lbs (15.4 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	190°F (87.8 °C)

CERTIFICATIONS

IP67 Def Stan 81-41

OTHER

Master Pack	1
Nameplate	yes
Reduced Area	yes
Military	yes

ACCESSORIES



0351 7 pc. Replacement Foam Set



1506TSA TSA Lock



0353 Replacement O-ring



1500D Desiccant Silica Gel



0355 Padded Divider Set



0357 Cube Case Mobility Package



1507 Quick Mounts - set of 4

Peli c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 09-17-25