



SUPER-V-SERIES-5U

Super V

5U

- SUPER V-SERIES 5U, 2112-02/29/05W
- Fixed square hole frame for universal equipment fit
- 2" Front Lid, 5" Rear Lid
- Anti-reflective black hardware
- Coupling catches for secure stacking
- Available in 3U, 4U, 5U, 7U, 9U, 11U, and 14U
- Weight ranges for 7U - 14U = 100-170lbs per case
- Molded in rear edge casters with handles on the lid for ease of movement
- Comfort Grip plastic handles
- Metric M6 clip nuts for more flexibility in mounting equipment
- Engineered to provide secure transport for rack mountable electronics
- Equipment payload weight ranges for 3U - 5U = 80-100 lbs. (36-45 kg) per case
- Lid hangers for lid storage while in use
- Sealed gasket and PRV keeps container watertight and eliminates over pressurization
- REACH and RoHS compliant



DIMENSIONS

Exterior (LxWxD)	38.50 x 28.30" x 14.90 (97.8 x 71.9 x 37.8 cm)
Rack Height	8.75" (22.2 cm)
Rack Depth	24.00" (61 cm)
Interior Lid Depth	2.20" (5.6 cm)
Interior Back Lid Depth	5.20" (13.2 cm)

MATERIALS

Body	RotoMolded Polyethylene
O-Ring	Silicone Sponge
Purge Body	Aluminum
Hardware	Stainless Steel (Black Oxide) / RoHS Nickel Black
Frame	Steel (Clear Coated)

COLOURS

■ Black

WEIGHT

Weight	55.00 lbs (24.9 kg)
---------------	---------------------

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

info@peli.com • www.peli.com

Document created on 04-21-25