

1505

Air

The 1505 Air case is a versatile, shallow attaché-style case with built-in functionality to support panel mounting in the lid and base. Protect laptops and sensitive electronics or leverage the out-of-the-box panel mounting capability to engineer your own mobile communications system, cradlepoint, or battery charging station. Whether you're a construction professional transporting your laptop to the site, a law enforcement team relying on a cradlepoint to maintain communications, or prototyping a new medical device, the 1505 Air case delivers the ultimate combination of durability, portability, and versatility.

- Integrated bezel system for panel mounting
- · Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified
- Super-light proprietary HPX^{2™} Polymer up to 40% lighter
- Press and Pull[™] Latches
- Automatic Pressure Equalization Valve balances interior pressure, keeps water out
- Fold down overmolded handle
- Waterproof O-ring seal
- Stainless steel padlock protectors
- · Limited Lifetime Warranty



CONFIGURATIONS



1505 Standard



1505NF No Foam



1505WF With Foam



1505TP With TrekPak Divider System

DIMENSIONS

Interior (L×W×D) 18.29 x 13.26" x 5.46 (46.5 x 33.7 x 13.9 cm) Exterior (L×W×D) 20.22 x 16.38" x 6.10 (51.4 x 41.6 x 15.5 cm)

 Lid Depth
 1.93" (4.9 cm)

 Bottom Depth
 3.53" (9 cm)

 Total Depth
 5.46" (13.9 cm)

 Int Volume
 0.77 ft³ (0.022 m³)

 Padlock Hole Diameter
 5/16" (12.7 cm)

MATERIALS

Body Proprietary Polypropylene Blend

Latch ABS O-Ring EPDM

Pins Stainless Steel

Foam Polyurethane

ABS

Purge Body

Purge VentHi-Flow Gore-Tex 3 Micron Hydrophobic Non-WovenHandlePolypropylene and Thermoplastic Rubber Side Handle

COLOURS



WEIGHT

 Weight With Foam
 6.55 lbs (3 kg)

 Weight Empty
 5.80 lbs (2.6 kg)

 Buoyancy
 54.00 lbs (24.5 kg)

TEMPERATURE

Minimum Temperature 0°F (-17.8 °C) **Maximum Temperature** 140°F (60 °C)

ACCESSORIES







1472 Shoulder Strap

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 09-06-25