

1640

Protector

Transport Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

- 4 strong polyurethane wheels with stainless steel bearings
- Watertight, crushproof, and dustproof
- 3 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve balances interior pressure, keeps water out
- · Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Retractable extension trolley handle
- Stainless steel padlock protectors



CONFIGURATIONS



1640 Standard



1644With Padded Dividers



1640NF No Foam



1640WF With Foam

DIMENSIONS

 Interior (L×W×D)
 23.70 x 24.00" x 13.90 (60.2 x 61 x 35.3 cm)

 Exterior (L×W×D)
 27.20 x 27.50" x 16.30 (69.1 x 69.9 x 41.4 cm)

 Lid Depth
 2.00" (5.1 cm)

 Bottom Depth
 11.90" (30.2 cm)

 Total Depth
 13.9" (35.3 cm)

 Int Volume
 4.58 ft³ (0.13 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

MATERIALS

Body Polypropylene

Latch ABS
O-Ring Polymer
Pins Stainless Steel
Foam 1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS



WEIGHT

 Weight With Foam
 38.00 lbs (17.2 kg)

 Weight Empty
 34.00 lbs (15.4 kg)

 Buoyancy
 365.00 lbs (165.6 kg)

 Master Pack Weight
 50.00 lbs (22.7 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

CERTIFICATIONS

IP67

Def Stan 81-41

OTHER

Wheels 4
Extendable Handle yes
Master Pack 1
Nameplate yes
Reduced Area yes

ACCESSORIES



0373Replacement O-ring



0379 Lid Organizer



1641 5 pc. Replacement Foam Set



1645 Padded Divider Set



1507 Quick Mounts - set of 4



1506TSA TSA Lock



1500D Desiccant Silica Gel

Document created on 08-14-25