



1780

Protector

Transport Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived. Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- **4 strong polyurethane wheels with stainless steel bearings**
- **The new class of XXL Peli Transport Cases**
- **Watertight, crushproof, and dustproof**
- 50/50 lid-to-base ratio for easy loading
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Completely detachable lid for full access
- Easy open double-throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel padlock protectors
- Peli's legendary lifetime guarantee**
- * Where applicable by law



CONFIGURATIONS



1780
Standard



1780NF
No Foam



1780WF
With Foam

DIMENSIONS

| | |
|------------------------------|-------------------------------------------------|
| Interior (L×W×D) | 41.12 x 21.54" x 14.88 (104.4 x 54.7 x 37.8 cm) |
| Exterior (L×W×D) | 44.90 x 25.32" x 16.50 (114 x 64.3 x 41.9 cm) |
| Lid Depth | 7.58" (19.3 cm) |
| Bottom Depth | 7.30" (18.5 cm) |
| Total Depth | 14.88" (37.8 cm) |
| Int Volume | 7.63 ft³ (0.216 m³) |
| Padlock Hole Diameter | 0.31" (0.8 cm) |

MATERIALS

| | |
|---------------|---------------|
| Body | Polypropylene |
| Latch | EXL |
| O-Ring | Polymer |

| | |
|-------------------|--------------------------------|
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

COLOURS

■ Black

WEIGHT

| | |
|---------------------------|-----------------------|
| Weight With Foam | 49.00 lbs (22.2 kg) |
| Weight Empty | 38.40 lbs (17.4 kg) |
| Buoyancy | 500.00 lbs (226.8 kg) |
| Master Pack Weight | 56.00 lbs (25.4 kg) |

TEMPERATURE

| | |
|----------------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 190°F (87.8 °C) |

CERTIFICATIONS

Def Stan 81-41

OTHER

| | |
|--------------------|-----|
| Wheels | 4 |
| Master Pack | 1 |
| Nameplate | yes |

ACCESSORIES



1781
6 pc. Replacement Foam Set



1783
Replacement O-ring



1506TSA
TSA Lock



1500D
Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 09-16-25