



1550EU

Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

These tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.



- **Watertight, crushproof, and dustproof**

- 2 level Pick N Pluck™ with convoluted lid foam
- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Comfortable rubber over-molded handle
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel hardware and padlock protectors
- Made in Germany
- Peli's legendary lifetime guarantee**
- * Where applicable by law

CONFIGURATIONS



1550EU
Standard



1554
With Padded Dividers



1550NF
No Foam



1550WF
With Foam

DIMENSIONS

| | |
|------------------------------|---|
| Interior (LxWxD) | 18.63 x 14.18" x 7.71 (47.3 x 36 x 19.6 cm) |
| Exterior (LxWxD) | 20.66 x 17.12" x 8.51 (52.5 x 43.5 x 21.6 cm) |
| Lid Depth | 1.75" (4.4 cm) |
| Bottom Depth | 5.87" (14.9 cm) |
| Total Depth | 7.62" (19.4 cm) |
| Int Volume | 1.18 ft³ (0.033 m³) |
| Padlock Hole Diameter | 5/16" (12.7 cm) |

MATERIALS

| | |
|---------------|---------------------|
| Body | Polypropylene |
| Latch | ABS |
| O-Ring | Polymer |
| Pins | Stainless Steel |
| Foam | 1.3 lb Polyurethane |

| | |
|-------------------|--------------------------------|
| Purge Body | ABS |
| Purge Vent | 3 Micron Hydrophobic Non-Woven |

COLOURS

| | | | |
|---|---|---|---|
| Black | Desert Tan | Orange | OD Green |
| Silver | Yellow | | |

WEIGHT

| | |
|-------------------------|---------------------|
| Weight With Foam | 11.90 lbs (5.4 kg) |
| Weight Empty | 10.58 lbs (4.8 kg) |
| Buoyancy | 69.89 lbs (31.7 kg) |

TEMPERATURE

| | |
|----------------------------|-----------------|
| Minimum Temperature | -40°F (-40 °C) |
| Maximum Temperature | 190°F (87.8 °C) |

CERTIFICATIONS

| |
|-----------------------|
| IP67 |
| MIL C-4150J |
| Def Stan 81-41 |
| ATA 300 |

OTHER

| | |
|--------------------|-----|
| Master Pack | 2 |
| Nameplate | yes |
| Military | yes |

ACCESSORIES

| | | | | | | | | | |
|---|---|---|--|---|--------------------------------------|--|---|---|---|
|  | 1551 4 pc. Replacement Foam Set |  | 1550PF Special Application Panel Frame |  | 1553 Replacement O-ring |  | 1555 Padded Divider Set |  | 1550EUTP TrekPak Case Divider Kit |
|  | 1507 Quick Mounts - set of 4 |  | 1506TSA TSA Lock |  | 1500D Desiccant Silica Gel |  | 1555EMS EMS Accessory Set (Lid Organizer and Divider Set) | | |

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 01-18-26