

AL5924-1009

For over 65 years Peli's roto-molded cases have been relied upon for an unmatched range of engineered solutions for the Military and Medical, Telecommunications and High Tech industries. Peli offers over 350 case sizes with unlimited case configurations using standard case options. Either build your own case or our engineers will customize a solution specific to your performance requirements.

Our roto molded cases pass MIL-STD 810D and E, MIL-STD 810E MIL-STD-210C, ASTM E96; FED-STD-101 and ATA 300 testing.

This level of performance ensures your equipment is safe from any unforeseen elements when deploying, transporting or storing your most valuable assets.

- One-piece construction, molded from lightweight, high-impact polyethylene
- Molded-in, tongue-in-groove gasketed "parting lines" provide for weather resistance.
- Reinforced corners and edges for additional impact protection when cases are dropped.
- Hardware attaches to molded-in metal inserts to provide pull-out strength and load spreading so hardware never fails.
- Molded-in ribs and corrugations offer case strength for secure and heavy weight stacking capacity
- Recessed hardware, with its engineered shoulder geometry, reduces shear forces that prevents lid separation after impact and controls pressure on the gasket to maintain a weatherproof seal.



GRÖSSE

INNERE 59.30 x 24.30" x 19.30 (150.6 x 61.7 x 49 cm) **AUSSEN** 62.30 x 27.30" x 21.60 (158.2 x 69.3 x 54.9 cm)

 Deckeltiefe
 9.20" (23.4 cm)

 Bodentiefe
 10.10" (25.7 cm)

 Gesamttiefe
 19.3" (49 cm)

 Innenvolumen
 16.09 ft³ (0.456 m³)

MATERIALEN

Gehäuse RotoMolded Polyethylene
Verschluss Steel (Nickel-black Plated)

O-Ring Dichtung Silicone Sponge

Schaumstoff

No Foam, empty case standard

Optional PE and PU, 1 and 2 lb. options filled and lined

Ausgleichsschraube Aluminum

Handgriff Heavy Duty Injection Molded Standard

Beschläge Yellow Carbon Steel Standard

FARBEN

GEWICHT

Gewicht 61.30 lbs (27.8 kg)

TEMPERATUR

 min. Temperatur
 -20°F (-28.9 °C)

 max. Temperatur
 140°F (60 °C)

ANDERE

Militär ja

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 11-07-25