



1930Z0

L1™

Same features as L1™ 1930 LED with static-dissipation materials body. Being certified to ATEX safe for use in high-risk hazardous locations, Zone 0 (Category 1) areas, L1™ 1930Z0 LED is ideal for professionals who work in chemical, pharmaceutical, power, oil and gas, and fire rescue industries.



DIMENSIONS

Length 2.64" (6.7 cm)

MATERIALS

Body Anti-static Impact Modified PC/PBT
O-Ring Ethylene Propylene
Lens Polycarbonate (PC)
Shroud Anti-static Impact Modified PC/PBT
Contact Spring Retainer Phosphore Bronze

COLOURS

■ Gray

LIGHT SPECS

Lamp Type LED

POWER

Battery Size LR 44
Battery Type Alkaline
Battery Quantity 4
Batteries Included yes
Volts 6.0v

WEIGHT

Weight With Batteries 0.9 oz (26 gr)
Weight Without Batteries 0.6 oz (17 gr)
Packaged Weight 0.8 oz (23 gr)

SWITCH






Switch Type Push Button Tail
Light Modes On / Off

CERTIFICATIONS

ATEX Zone 0

OTHER

Minimum Pack 12
Military yes
Package Code C

FL1 STANDARD	HIGH
	12 LUMENS
	4h 15mins
	17m
	70cd
	IPX4

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 04-24-25