

# 1470 Protector Laptop Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

#### Double safety locking latches with keys

Automatic pressure equalization valve - balances interior pressure, keeps water out

- Comfortable rubber over-molded handle
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck<sup>™</sup> with convoluted lid foam
- Peli's legendary lifetime guarantee\*\*
- \* Where applicable by law



### CONFIGURATIONS



1470 Standard



**1470NF** No Foam



1470WF With Foam

### DIMENSIONS

Interior (L×W×D)	15.70 x 10.70" x 3.87 (39.9 x 27.2 x 9.8 cm)
Exterior (L×W×D)	16.88 x 13.23" x 4.47 (42.9 x 33.6 x 11.4 cm)
Lid Depth	1.47" (3.7 cm)
Bottom Depth	2.40" (6.1 cm)
Total Depth	3.87" (9.8 cm)
Int Volume	0.38 ft³ (0.011 m³)
Padlock Hole Diameter	0.25" (0.6 cm)

### MATERIALS

Body	ABS
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

# COLOURS

#### Black

### WEIGHT

Weight With Foam	5.51 lbs (2.5 kg)
Weight Empty	4.28 lbs (1.9 kg)
Buoyancy	24.91 lbs (11.3 kg)
Master Pack Weight	22.20 lbs (10.1 kg)

#### TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	190°F (87.8 °C)

#### CERTIFICATIONS

MIL C-4150J

#### OTHER

Master Pack	4
Nameplate	yes
Military	yes

# ACCESSORIES



**1471** 3 pc. Replacement Foam Set

COLOR H

**1506TSA** TSA Lock



**1472** Shoulder Strap



1500D Desiccant Silica Gel



1473 Replacement O-ring



1470PF Special Application Panel Frame



1507 Quick Mounts - set of 4

Peli c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 07-24-25