

1730

Protector

Transport Case

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

• Watertight, crushproof, and dustproof

- 5-piece foam set
- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- · Fold down handles
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Optional Humidity gauge changes color above 40%
- Optional Manual Pressure Equalization Valve
- Stainless steel hardware and padlock protectors



CONFIGURATIONS







1730NF No Foam



1730WF With Foam

DIMENSIONS

 Interior (L×W×D)
 34.00 x 24.00" x 12.50 (86.4 x 61 x 31.8 cm)

 Exterior (L×W×D)
 37.50 x 27.13" x 14.37 (95.3 x 68.9 x 36.5 cm)

 Lid Depth
 2.50" (6.4 cm)

 Bottom Depth
 10.00" (25.4 cm)

 Total Depth
 12.5" (31.8 cm)

 Int Volume
 5.9 ft³ (0.167 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

MATERIALS

Body Polypropylene

Latch ABS
O-Ring Polymer
Pins Stainless Steel
Foam 1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

COLOURS



WEIGHT

 Weight With Foam
 38.00 lbs (17.2 kg)

 Weight Empty
 30.00 lbs (13.6 kg)

 Buoyancy
 416.00 lbs (188.7 kg)

 Master Pack Weight
 43.00 lbs (19.5 kg)

TEMPERATURE

Minimum Temperature -40°F (-40 °C) **Maximum Temperature** 190°F (87.8 °C)

CERTIFICATIONS

IP67

OTHER

Wheels 2 Master Pack 1 Nameplate yes

ACCESSORIES



1731 5 pc. Replacement Foam Set



1733 Replacement O-ring



1506TSA TSA Lock



1500D Desiccant Silica Gel

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999 info@peli.com • www.peli.com

Document created on 09-05-25