



## 472-PWC-SCBA

### Mobile Medical™

SCBA Double Tank Case

This Peli™ iM2950 case securely transports two SCBA tanks. This watertight & crushproof case features a hinged lid, five Press & Pull™ latches, two double-layered soft grip handle, two padlock-able hasps, a Vortex™ valve and comes with a lifetime guarantee.

- SCBA cylinder case holds two tanks up to 7-inches (17.8cm) in diameter
- Tanks sit in foam cradles and are held in place by adjustable straps



### DIMENSIONS

|                         |  |
|-------------------------|--|
| <b>Interior (L×W×D)</b> | 29.00 x 18.00" x 10.50 (73.7 x 45.7 x 26.7 cm) |
| <b>Exterior (L×W×D)</b> | 31.30 x 20.40" x 12.20 (79.5 x 51.8 x 31 cm)   |
| <b>Lid Depth</b>        | 2.00" (5.1 cm)                                 |
| <b>Bottom Depth</b>     | 8.50" (21.6 cm)                                |
| <b>Total Depth</b>      | 10.5" (26.7 cm)                                |
| <b>Int Volume</b>       | 3.17 ft <sup>3</sup> (0.09 m <sup>3</sup> )    |

### MATERIALS

|                         |  |
|-------------------------|--|
| <b>Body</b>             | Injection Molded HPX™ high performance resin |
| <b>Latch</b>            | Valox - Polybutylene Terephthalate (PBT)     |
| <b>Latch (Alt)</b>      | Xenox - Polyester/Polycarbonate blend        |
| <b>O-Ring</b>           | EPDM   |
| <b>Pins</b>             | Stainless Steel                              |
| <b>Foam</b>             | Aluminum                                     |
| <b>Purge Body</b>       | 1.3/1.35 polyester                           |
| <b>Purge Body (Alt)</b> | Valox - Polybutylene Terephthalate (PBT)     |
| <b>Purge Vent</b>       | Xenox - Polyester/Polycarbonate blend        |

### COLOURS

|         |            |
|---------|------------|
| ■ Black | ■ OD Green |
|---------|------------|

### TEMPERATURE

|                            |                  |
|----------------------------|------------------|
| <b>Minimum Temperature</b> | -20°F (-28.9 °C) |
| <b>Maximum Temperature</b> | 140°F (60 °C)    |

#### Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 03-31-25*