



# 1930Z0

L1™

Same features as L1™ 1930 LED with static-dissipation materials body. Being certified to ATEX safe for use in high-risk hazardous locations, Zone 0 (Category 1) areas, L1™ 1930Z0 LED is ideal for professionals who work in chemical, pharmaceutical, power, oil and gas, and fire rescue industries.



## DIMENSIONS

**Length** 2.64" (6.7 cm)

## MATERIALS

**Body** Anti-static Impact Modified PC/PBT  
**O-Ring** Ethylene Propylene  
**Lens** Polycarbonate (PC)  
**Shroud** Anti-static Impact Modified PC/PBT  
**Contact Spring Retainer** Phosphore Bronze

## COLOURS

■ Gray

## LIGHT SPECS

**Lamp Type** LED

## POWER

**Battery Size** LR 44  
**Battery Type** Alkaline  
**Battery Quantity** 4  
**Batteries Included** yes  
**Volts** 6.0v

## WEIGHT

**Weight With Batteries** 0.9 oz (26 gr)  
**Weight Without Batteries** 0.6 oz (17 gr)  
**Packaged Weight** 0.8 oz (23 gr)

## SWITCH

**Switch Type** Push Button Tail  
**Light Modes** On / Off

## CERTIFICATIONS

---

**ATEX Zone 0**

## OTHER

---

**Minimum Pack** 12  
**Military** yes  
**Package Code** C

FL1 STANDARD	HIGH
	12 LUMENS
	4h 15mins
	17m
	70cd
	IPX4

---

**Peli**

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999  
[info@peli.com](mailto:info@peli.com) • [www.peli.com](http://www.peli.com)

*Document created on 07-06-26*