



1930Z0

L1™

Same features as L1™ 1930 LED with static-dissipation materials body. Being certified to ATEX safe for use in high-risk hazardous locations, Zone 0 (Category 1) areas, L1™ 1930Z0 LED is ideal for professionals who work in chemical, pharmaceutical, power, oil and gas, and fire rescue industries.



DIMENSIONS

Length	2.64" (6.7 cm)
--------	----------------

MATERIALS

Body	Anti-static Impact Modified PC/PBT
O-Ring	Ethylene Propylene
Lens	Polycarbonate (PC)
Shroud	Anti-static Impact Modified PC/PBT
Contact Spring Retainer	Phosphore Bronze

COLOURS

Gray

LIGHT SPECS

Lamp Type	LED
-----------	-----

POWER

Battery Size	LR 44
Battery Type	Alkaline
Battery Quantity	4
Batteries Included	yes
Volts	6.0v

WEIGHT

Weight With Batteries	0.9 oz (26 gr)
Weight Without Batteries	0.6 oz (17 gr)
Packaged Weight	0.8 oz (23 gr)

SWITCH

Switch Type	Push Button Tail
Light Modes	On / Off

CERTIFICATIONS

ATEX Zone 0

OTHER

Minimum Pack	12
Military	yes
Package Code	C

FL1 STANDARD	HIGH
	12 LUMENS
	4h 15mins
	17m
	70cd
	IPX4

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 08-12-25