



2220Z1 VB3™

The VB3™ 2220Z1 LED light has dual super bright white LEDs that may never need replacing and provide over 30 hours of run time. The light is ATEX safe for use in hazardous Zone 1 (Category 2) locations. The VB3™ 2220Z1 LED is ideal for professionals who work in areas with high risk of explosion such as chemical, pharmaceutical, power, oil and gas, and fire rescue.



DIMENSIONS

| | |
|---------------|----------------|
| Length | 3.50" (8.9 cm) |
|---------------|----------------|

MATERIALS

| | |
|--------------------------------|------------------------------------|
| Body | Anti-static Impact Modified PC/PBT |
| Clip | Anti-static Impact Modified PC/PBT |
| Contact Spring Retainer | Stainless Steel |

COLOURS

| | |
|---|--|
|  Black |  High Visibility Yellow |
|---|--|

LIGHT SPECS

| | |
|------------------|-----|
| Lamp Type | LED |
|------------------|-----|

POWER

| | |
|---------------------------|---------|
| Battery Size | CR2032 |
| Battery Type | Lithium |
| Battery Quantity | 2 |
| Batteries Included | yes |
| Volts | 3.0v |

WEIGHT

| | |
|---------------------------------|----------------|
| Weight With Batteries | 1.0 oz (28 gr) |
| Weight Without Batteries | 0.9 oz (26 gr) |
| Packaged Weight | 1.7 oz (48 gr) |

SWITCH

| | |
|--------------------|-----------------------|
| Switch Type | Head Flip to Activate |
|--------------------|-----------------------|

Light Modes

On / Off

CERTIFICATIONS

ATEX Zone 1

OTHER

Minimum Pack






6

Military

yes

Package Code

C

| FL1 STANDARD | HIGH |
|---|-------------|
|  | 8 LUMENS |
|  | 8h 0mins |
|  | 19m |
|  | 92cd |
|  | IPX4 |

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999

info@peli.com • www.peli.com

Document created on 07-17-24