



2460Z1 StealthLite™

The rechargeable version of the StealthLite™ 2410 LED. The StealthLite™ Rechargeable 2460Z1 LED uses the 2469P NiMH battery and comes with the charger base unit cat # 2480F that can be installed at home or work using the 220V transformer cat # 2468Z1. Certified to ATEX Zone 1 (Category 2). Note, this charger base does not work on 12v systems.



DIMENSIONS

Length	7.00" (17.8 cm)
---------------	-----------------

MATERIALS

Body	Anti-static Impact Modified PC/PBT
O-Ring	Ethylene Propylene
Lens	Polycarbonate (PC)
Shroud	Anti-static Impact Modified PC/PBT
Contact Spring Retainer	Stainless Steel / Phosphore Bronze

COLOURS

 High Visibility Yellow
--

LIGHT SPECS

Lamp Type	LED
------------------	-----

POWER

Battery Size	AA
Battery Type	NiMH
Battery Quantity	4
Batteries Included	yes
Rechargeable	yes
Charge Time	8 hrs
Volts	4.8v

WEIGHT

Weight With Batteries	7.8 oz (221 gr)
Weight Without Batteries	4.4 oz (125 gr)
Packaged Weight	1.4 oz (40 gr)

SWITCH

Switch Type	One-handed Safety Switch
Light Modes	On / Off

CERTIFICATIONS

ATEX Zone 1	
OTHER	

Minimum Pack	1
Military	yes
Package Code	C

FL1 STANDARD	HIGH
	181 LUMENS
	5h 0mins
	181m
	8235cd
	IPX7

ACCESSORIES



0770
Helmet Light Holder



2480F
Deck/Dash Charger Base Unit



2469P
Replacement Battery

info@peli.com • www.peli.com

Document created on 02-15-26