



1506

Air

Peli understands that finding the right protection, with the perfect fit for your gear, is a priority. Peli™ Air began with long protection and quickly grew to offer you deep protection. The time has come to combine those two in order to create Peli's new Long/Deep Series. Gone are the days of dangerously forcing your equipment into the wrong size case or leaving it unprotected with no other options. With Peli's Long/Deep series, we've created the missing link so that no matter the demands of your gear, Peli has you covered.

- Automatic pressure equalization valve - balances interior pressure, keeps water out
- Fold down over-molded handle
- Stainless steel padlock protectors
- Super-light proprietary HPX Polymer makes this case up to 40% lighter than the competition
- Limited Lifetime Warranty
- Super-light proprietary HPX²™ Polymer - up to 40% lighter
- Waterproof O-ring seal
- User-customizable Pick N Pluck™ foam
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified



CONFIGURATIONS



1506
Standard



1506WF
With Foam



1506NF
No Foam



1506TP
With TrekPak Divider System

DIMENSIONS

Interior (LxWxD)	18.70 x 9.40" x 7.80 (47.5 x 23.9 x 19.8 cm)
Exterior (LxWxD)	20.12 x 12.02" x 8.56 (51.1 x 30.5 x 21.7 cm)
Lid Depth	2.00" (5.1 cm)
Bottom Depth	5.80" (14.7 cm)
Total Depth	7.8" (19.8 cm)
Int Volume	0.79 ft ³ (0.022 m ³)
Padlock Hole Diameter	0.31" (0.8 cm)

MATERIALS

Body	Proprietary Polypropylene Blend
Latch	ABS
O-Ring	EPDM
Purge Body	ABS

Purge Vent

Hi-Flow Gore-Tex 3 Micron Hydrophobic Non-Woven

COLOURS

■ Black

WEIGHT

Weight With Foam	6.30 lbs (2.86 kg)
Weight Empty	5.35 lbs (2.43 kg)
Buoyancy	51.69 lbs (23.45 kg)

TEMPERATURE

Minimum Temperature	0°F (-17.8 °C)
Maximum Temperature	140°F (60 °C)

ACCESSORIES



1506AirFS
4 pc. Replacement Foam Set



1506TPKIT
TrekPak Case Divider Kit



RucPac-Pro-1
RucPac Pro Hardcase Backpack
Conversion



1506TPDIV
Extra TrekPak Dividers

Peli

c/ Provença, 388, Planta 7 • Barcelona, Spain 08025 • Phone: +34 934 674 999
info@peli.com • www.peli.com

Document created on 04-26-26