

# 1506

### Air

Peli understands that finding the right protection, with the perfect fit for your gear, is a priority. Peli™ Air began with long protection and quickly grew to offer you deep protection. The time has come to combine those two in order to create Peli's new Long/Deep Series. Gone are the days of dangerously forcing your equipment into the wrong size case or leaving it unprotected with no other options. With Peli's Long/Deep series, we've created the missing link so that no matter the demands of your gear, Peli has you covered.

- Automatic pressure equalization valve balances interior pressure, keeps water out
- Fold down over-molded handle
- Stainless steel padlock protectors
- $\bullet$  Super-light proprietary HPX Polymer makes this case up to 40% lighter than the competition
- Limited Lifetime Warranty
- Super-light proprietary HPX<sup>2™</sup> Polymer up to 40% lighter
- Waterproof O-ring seal
- User-customizable Pick N Pluck<sup>™</sup> foam
- Waterproof, crushproof, dustproof
- IP67 & MIL-SPEC certified



## **CONFIGURATIONS**



**1506** Standard



1506WF With Foam



**1506NF** No Foam



**1506TP**With TrekPak Divider System

## **DIMENSIONS**

Interior (L×W×D) 18.70 x 9.40" x 7.80 (47.5 x 23.9 x 19.8 cm) Exterior (L×W×D) 20.12 x 12.02" x 8.56 (51.1 x 30.5 x 21.7 cm)

 Lid Depth
 2.00" (5.1 cm)

 Bottom Depth
 5.80" (14.7 cm)

 Total Depth
 7.8" (19.8 cm)

 Int Volume
 0.79 ft³ (0.022 m³)

 Padlock Hole Diameter
 0.31" (0.8 cm)

## **MATERIALS**

**Body** Proprietary Polypropylene Blend

Latch ABS
O-Ring EPDM
Purge Body ABS

# **COLOURS**



## WEIGHT

 Weight With Foam
 6.30 lbs (2.9 kg)

 Weight Empty
 5.35 lbs (2.4 kg)

 Buoyancy
 51.69 lbs (23.4 kg)

## **TEMPERATURE**

**Minimum Temperature** 0°F (-17.8 °C) **Maximum Temperature** 140°F (60 °C)

## **ACCESSORIES**



**1506AirFS** 4 pc. Replacement Foam Set



**1506TPKIT** TrekPak Case Divider Kit



RucPac-Pro-1 RucPac Pro Hardcase Backpack Conversion



**1506TPDIV** Extra TrekPak Dividers

#### Peli

Document created on 09-17-25