

# 1200

## **Protector**

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware.

#### · Watertight, crushproof, and dustproof

- Automatic pressure equalization valve balances interior pressure, keeps water out
- Easy open double-throw latches
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck<sup>™</sup> with convoluted lid foam
- Peli's legendary lifetime guarantee\*\*
- \* Where applicable by law



#### **CONFIGURATIONS**



1200 Standard



1200NF No Foam



1200WF With Foam

#### **DIMENSIONS**

 Interior (L×W×D)
 9.31 x 7.13" x 4.12 (23.6 x 18.1 x 10.5 cm)

 Exterior (L×W×D)
 10.67 x 9.75" x 4.86 (27.1 x 24.8 x 12.3 cm)

 Lid Depth
 1.18" (3 cm)

 Bottom Depth
 2.93" (7.4 cm)

 Total Depth
 4.11" (10.4 cm)

 Int Volume
 0.16 ft³ (0.005 m³)

## **MATERIALS**

**Body** Polypropylene

Latch ABS
O-Ring Polymer
Pins Stainless Steel
Foam 1.3 lb Polyurethane

Purge Body ABS

Purge Vent 3 Micron Hydrophobic Non-Woven

## **COLOURS**



Desert Tan



Silver

# WEIGHT

 Weight With Foam
 2.87 lbs (1.3 kg)

 Weight Empty
 2.65 lbs (1.2 kg)

 Buoyancy
 12.02 lbs (5.5 kg)

 Master Pack Weight
 25.00 lbs (11.3 kg)

## **TEMPERATURE**

 $\begin{array}{ll} \mbox{Minimum Temperature} & -40\,^{\circ}\mbox{F} \; (-40\,^{\circ}\mbox{C}) \\ \mbox{Maximum Temperature} & 190\,^{\circ}\mbox{F} \; (87.8\,^{\circ}\mbox{C}) \\ \end{array}$ 

## **CERTIFICATIONS**

**IP67** 

Def Stan 81-41

#### **OTHER**

Master Pack6Militaryyes

## **ACCESSORIES**



**1201** 3 pc. Replacement Foam Set



**1203** Replacement O-ring



**1200PF**Special Application Panel Frame



**1507** Quick Mounts - set of 4



1506TSA TSA Lock



**1500D** Desiccant Silica Gel