

CLASSIC-V-SERIES-3U

Classic V

• Engineered to provide secure transport for rack mountable electronics

• Available in 3U, 4U, 5U, 7U, and 9U

• Equipment payload weight ranges for 3U - 5U = 80-100 lbs. (36-45 kg) per case

• Equipment payload weight ranges for 7U - 9U = 100-170 lbs. (45-77 kg) per case

Black case with Anti-Reflective zinc cobalt black (HCB) catch-and-strike hardware

- 2 Lockable Cable Catches per lid to provide security for your equipment
- Black stainless steel handles
- Molded stacking ribs and coupling catches to secure cases when stacked
 Lid bangers for lid starage while in use
- Lid hangers for lid storage while in use

 \cdot 19" (48 cm) wide, 33" (83 cm) deep fixed square hole frame for universal equipment fit

• Choice of SAE 10-32 or Metric M6 clip nuts

Sealed gasket and PRV keeps container watertight and eliminates over pressurization

• 4 removable 3.5" (8.9 cm) heavy duty bottom casters

• REACH and RoHs compliant

DIMENSIONS

Exterior (L×W×D)	45.80 x 27.00" x 12.30 (116.3 x 68.6 x 31.2 cm)
Rack Height	5.25" (13.3 cm)
Rack Depth	33.00" (83.8 cm)
Interior Lid Depth	2.50" (6.4 cm)
Interior Back Lid Depth	5.25" (13.3 cm)

MATERIALS

Body	RotoMolded Polyethylene
O-Ring	Silicone Sponge
Purge Body	Aluminum
Hardware	Stainless Steel (Black Oxide) / RoHs Nickel Black
Frame	Steel (Clear Coated)

COLOURS

Black

WEIGHT

Weight

51.00 lbs (23.1 kg)

Document created on 07-13-25